

W170C W190C W230C

PRELIMINARY



	W170C	W190C	W230C
BUCKET CAPACITY	2.5 m ³	3.25 m ³	3.6 m ³
ENGINE POWER	133 kW - 179 hp	154 kW - 206 hp	168 kW - 225 hp
OPERATING WEIGHT	14.292 kg	17.633 kg	19.857 kg



BUILT AROUND YOU

W170C/W190C/W230C

10% LESS FUEL CONSUMPTION
30% MORE PRODUCTIVITY
HIGHEST RELIABILITY WITH NEW HEAVY DUTY AXLES



Up to 10% fuel savings

Thanks to Tier 4 interim compliant Selective Catalytic Reduction (SCR technology), the new C Series delivers unprecedented fuel savings. The auto shutdown mode and the 5-speed optional transmission - together with lock-up torque converter and Power Inch - contribute to cuts by up to 10%.

Ready for hostile environments

Waste and scrap, compost and biogas, recycling at large require well-protected, heavy-duty machine design. Heavy Duty axles and hydraulic piping integrated within the machine body eliminate the risk of ruptures and snagging.

More grip and lifting force

The new C Series is equipped with the latest generation of Front & Rear Limited Slip Differential axles. Improved overall lifting force is complemented by a larger model lineup, with the new W230C delivering 12% more lifting force than the smaller model.

Perfected cooling in all conditions

The cooling module situated high in the chassis, between the cab and the engine, guarantees optimized air flow and constant engine cooling. It also provides natural balancing of the loader and low operating weights.



New cab for absolute comfort and safety

- New adjustable, heated seat
- Adjustable steering armrests and ergonomic control switches
- New air conditioning and heating system
- State-of-the-art sound system
- Perfect visibility on both sides of the front window
- Excellent rear visibility thanks to downward sloping hood

W170C/W190C/W230C



W170C	Z-Bar	TC	LR
Engine			
Net Rated HP	179 hp (133 kW)	179 hp (133 kW)	179 hp (133 kW)
Net Peak HP	179 hp (133 kW)	179 hp (133 kW)	179 hp (133 kW)
Operating Weight	14 292 kg	14 772 kg	14 462 kg
Bucket Capacity	2.49 m ³	2.49 m ³	2.49 m ³
Operating Load	5265 kg	4481 kg	4438 kg
Breakout Force	14 235 kg	12,637 kg	14 847 kg
Articulated Tipping Capacity	10 529 kg	8962 kg	8876 kg
Hinge Pin Height	3979 mm	4160 mm	4374 mm
W190C	Z-Bar	TC	LR
Engine			
Net Rated HP	206 hp (154 kW)	N.D.	206 hp (154 kW)
Net Peak HP	211 hp (158 kW)	N.D.	211 hp (158 kW)
Operating Weight	17 633 kg	N.D.	17 863 kg
Bucket Capacity	3.25 m ³	N.D.	2.7 m ³
Operating Load	6175 kg	N.D.	4967 kg
Breakout Force	16 029 kg	N.D.	18 731 kg
Articulated Tipping Capacity	12 349 kg	N.D.	9934 kg
Hinge Pin Height	4123 mm	N.D.	4564 mm
W230C	Z-Bar	TC	LR
Engine			
Net Rated HP	225 hp (168 kW)	N.D.	225 hp (168 kW)
Net Peak HP	242 hp (180 kW)	N.D.	242 hp (180 kW)
Operating Weight	19 857 kg	N.D.	19 857 kg
Bucket Capacity	3.63 m ³	N.D.	3.0 m ³
Operating Load	7123 kg	N.D.	5769 kg
Breakout Force	17 034 kg	N.D.	19 432 kg
Articulated Tipping Capacity	14 245 kg	N.D.	11 538 kg
Hinge Pin Height	4118 mm	N.D.	4560 mm

AT YOUR OWN DEALERSHIP

The information contained in this brochure is intended to be of general nature. The NEW HOLLAND KOBELCO CONSTRUCTION MACHINERY S.p.A. company may at any time and from time to time, for technical or other necessary reasons, modify any of the details or specifications of the product described in this brochure. Illustrations do not necessarily show products in standard conditions. The dimensions, weights and capacities shown herein, as well as any conversion data used, are approximate only and are subject to variations within normal manufacturing techniques.

Printed on recycled paper
CoC-FSC 000010 CQ Mixed sources



Published by NEW HOLLAND KOBELCO CONSTRUCTION MACHINERY S.p.A
Printed in Italy - MediaCross Firenze - Cod. 30620GB - Printed 02/11

